

TECHNICAL DATA SHEET

Rev. 8

MEDICAL DEVICE CLASS I

Eyepiece plasters white No-woven with protective gauze STERILE

9,5 x 6,5 cm

BASE MATERIAL

Data	Unit	Value	Tolerance
Material	-	Nowoven (TNT) white color	-
Composition	-	100% Polyester fibers	-
Grammage	g/m ²	48	±10%
Thickness	µm	500	±10%
Colour	-	White color	-
Tensile break	N/cm	≥ 6	-
Elongation to break	%	≥ 100	-

ADHESIVE

Data	Unit	Value	Tolerance
Type	-	Hot Melt acrylic crosslinking UV	-
Grammage	g/m ²	≥ 25	-
Adhesivity	N/cm	≥ 2,5	-


GAUZE

Data	Unit	Value	Tolerance
Type	-	Nonstick (sterilized)	-
1° layer composition (nonstick)	-	Perforated transparent LDPE	-
2° layer composition (protective)	-	Pulp and binders	-
Thickness	mm	4,00	±10%
Grammage	g/m ²	360	±10%
Absorbency	g/m ²	≥ 3500	-


SILICON PAPER

Data	Unit	Value	Tolerance
Type	-	One sided silicon paper	-
Grammage	g/m ²	≥ 50	-










PRIMARY PACKAGING "COLD SEALING"

Data	Unit	Value	Tolerance
Side 1	-	Neutral paper	-
Grammage	g/m ²	85	±10%
Side 2	-	Neutral paper	-
Grammage	g/m ²	85	±10%
Recycling codes	-		-

PACKAGING

Data	Unit	Value	Tolerance
Type	-	Case	-
Material	-	Cardboard	-
Grammage	g/m ²	240	±10%
Recycling code	-		-

MANDATORY WORDINGS

Data	Symbols	Definition
Manufacturer address		EUROSIREL S.p.A. - viale Europa, 30 - 20047 Cusago (MI) - Italy
CE mark		CE conformity mark
Sterilization		Sterilization ETO
Batch		YSSNNNN
Expiry date		YYYY-MM
Classification		Medical Device
Product shelf life	-	5 years
Conservation method		Keep in a cool and dry place, keep away from sunlight
Using		Monouse
REF code		OCSTXXXXXX
UDI-DI (Base) code	-	80179900CST75

13/04/2021 Cusago

Quality Department
 Eurosirel SpA