

Cerotti in TNT Bianco con Garza antiaderente

Astuccio da 15 cerotti formato 7 X 2 cm

Materiale base supporto

Dati	Unità	Valori	Tolleranza
Materiale	-	TNT Bianco	-
Composizione	-	Fibre di Poliestere 100 %	-
Grammatura	g/m ²	50	±10%
Spessore	µm	≥ 150	-
Colore	-	Bianco	-
Carico di rottura longitudinale	N/cm	≥ 6	-
Allungamento alla rottura	%	≥ 100	-

Adesivo

Dati	Unità	Valori	Tolleranza
Tipologia	-	Hot Melt acrilico ai raggi UV	-
Grammatura	g/m ²	≥ 35	-
Adesività	N/cm	≥ 3	-

Garza

Dati	Unità	Valori	Tolleranza
Tipo	-	Antiaderente	-
Composizione 1° strato (antiaderente)	-	LPDE trasparente perforato	-
Composizione 2° strato (assorbente)	-	Polpa di cellulosa e leganti	-
Spessore	mm	1,0	±10%
Grammatura	g/m ²	98	±10%
Assorbenza	g/m ²	≥ 600	-









Siliconata

Dati	Unità	Valori	Tolleranza
Tipo	-	Monosiliconata	-
Grammatura	g/m ²	≥ 50	-

Incarto primario "saldante a freddo"

Dati	Unità	Valori	Tolleranza
Lato 1	-	Carta Bianca	-
Lato 2	-	Carta Bianca	-

Packaging

Dati	Unità	Valori	Tolleranza
Tipo	-	Astuccio	-
Materiale	-	Cartoncino	-
Grammatura	g/m ²	260	±10%
Stampa Cartoncino	-	Consigli per l'uso e diciture di legge:     Indirizzo Fabbricante:   Lotto:(AFFNNNN).....  Scadenza:..... 	-

10.08.2015 Settimo Milanese

**Laboratorio e Qualità
Eurosirel SpA**

TECHNICAL DATA SHEET

Rev.1

MEDICAL DEVICE CLASS I

111021	Pharmadoc - Non woven white plaster with classic white gauze
---------------	---

20 pcs.

Material

Data	Unit	Value	Tolerance
Material	-	Non woven white	-
Composition	-	Polyester fibers	-
Weight	g/m ²	50	±10%
Thickness	µm	≥ 150	-
Color	-	white	-
Breaking Strength	N/cm	≥ 6	-
Elongation to break	%	≥ 100	-

Adhesive

Data	Unit	Value	Tolerance
Type	-	UV reactive copolymeric acrylic adhesive	-
Weight	g/m ²	≥ 35	-
Adhesivity	N/cm	≥ 3	-

Gauze

Data	Unit	Value	Tolerance
Type	-	Classic white gauze	-
Layer 1 Composition	-	Perforated transparent LDPE	-
Layer 2 Composition	-	Fluff pulp and bonding fibers	-
Thickness	mm	1,0	±10%
Weight	g/m ²	98	±10%
Absorption	g/m ²	≥ 600	-








Silicon Paper

Data	Unit	Value	Tolerance
Type	-	One sided silicon	-
Weight	g/m ²	≥ 50	-

Primary packaging "cold seal"

Data	Unit	Value	Tolerance
Side 1	-	Neutral Paper	-
Side 2	-	Neutral Paper	-

Packaging

Data	Unit	Value	Tolerance
Type	-	Case	-
Material	-	Cardboard	-
Weight	g/m ²	260	±10%
Printing on case	-	Advice for use and legal wording:     Manufacturer adress:  Lot:(AFFNNNN).....  Expyre:..... 	-

10.08.2015 Settimo Milanese

Quality Department
 Eurosirel SpA