

**SCHEDA TECNICA**

Rev.1

**DISPOSITIVO MEDICO CLASSE I**

**110130 Pharmadoct - AQUASTOP PU Trasparenti 20 assortiti**

20 pz.  
(15pz. 7x2 cm; 5pz. 3,8x3,8 cm)

**Materiale base supporto**

Dati	Unità	Valori	Tolleranza
Materiale	-	Film di poliuretano	-
Composizione	-	Film in PU trasparente con protezione in PE	-
Grammatura	g/m <sup>2</sup>	60	±10%
Spessore	µm	58 (riferito al PU)	±10%
Colore	-	Trasparente	-

**Adesivo**

Dati	Unità	Valori	Tolleranza
Tipologia	-	Hot Melt acrilico ai raggi UV	-
Grammatura	g/m <sup>2</sup>	≥ 35	-
Adesività	N/cm	≥ 3	-

**Garza**

Dati	Unità	Valori	Tolleranza
Tipo	-	Antiaderente	-
Composizione 1° strato (antiaderente)	-	LPDE trasparente perforato	-
Composizione 2° strato (assorbente)	-	Polpa di cellulosa e leganti	-
Spessore	mm	1,0	±10%
Grammatura	g/m <sup>2</sup>	98	±10%
Assorbenza	g/m <sup>2</sup>	≥ 600	-









**Siliconata**

Dati	Unità	Valori	Tolleranza
Tipo	-	Monosiliconata	-
Grammatura	g/m <sup>2</sup>	≥ 50	-

**Incarto primario "saldante a freddo"**

Dati	Unità	Valori	Tolleranza
Lato 1	-	Carta Bianca	-
Lato 2	-	Carta Bianca	-

**Packaging**

Dati	Unità	Valori	Tolleranza
Tipo	-	Astuccio	-
Materiale	-	Cartoncino	-
Grammatura	g/m <sup>2</sup>	260	±10%
Stampa Cartoncino	-	Consigli per l'uso e diciture di legge:     Indirizzo Fabbricante: .....   Lotto: .....(AFFNNNN).....  Scadenza:..... 	-

10.08.2015 Settimo Milanese

Laboratorio e Qualità  
Eurosirel SpA

**TECHNICAL DATA SHEET**

Rev.1

**MEDICAL DEVICE I CLASS**

**110130 Pharmadoct - AQUASTOP 20 PU Transparent Assorted Plasters**

20 pcs.  
(15pcs. 7x2 cm; 5pcs. 3,8x3,8 cm)

**Support**

Data	Unit	Value	Tolerance
Material	-	polyurethane film	-
Composition	-	transparent polyurethane film with PE carrier	-
Weight	g/m <sup>2</sup>	60	±10%
Thickness	µm	58	±10%
Color	-	transparent	-

**Adhesive**

Data	Unit	Value	Tolerance
Type	-	UV reactive copolymeric acrylic adhesive	-
Weight	g/m <sup>2</sup>	≥ 35	-
Adhesivity	N/cm	≥ 3	-

**Gauze**

Data	Unit	Value	Tolerance
Type	-	Classic white gauze	-
Layer 1 Composition	-	Perforated transparent LDPE	-
Layer 2 Composition	-	Fluff pulp and bonding fibers	-
Thickness	mm	1,0	±10%
Weight	g/m <sup>2</sup>	98	±10%
Absorption	g/m <sup>2</sup>	≥ 600	-








**Silicon Paper**

Data	Unit	Value	Tolerance
Type	-	One sided silicon	-
Weight	g/m <sup>2</sup>	≥ 50	-

**Primary packaging "cold seal"**

Data	Unit	Value	Tolerance
Side 1	-	Neutral Paper	-
Side 2	-	Neutral Paper	-

**Packaging**

Data	Unit	Value	Tolerance
Type	-	Case	-
Material	-	Cardboard	-
Weight	g/m <sup>2</sup>	260	±10%
Printing on case	-	Advice for use and legal wording:     Manufacturer address: .....  Lot: .....(AFFNNNN).....  Expyre:..... 	-

10.08.2015 Settimo Milanese

Quality Department  
Eurosirel SpA